

TECHNICAL DATA SHEET FOR
NIPPOLAC KITCHEN AND BATHROOM PAINT

DESCRIPTION	A high quality, mid sheen Acrylic paint with protection against fungal and algal growth, splashing of water, detergents and soap having excellent Mildew protection. It has resistance to conditions of high humidity, frequent temperature changes, condensed vapor and poor air circulation which promote mildew growth and paint deterioration. Recommended for Schools, Hospitals and Hotels, this mildew-free finish remains bright.
TYPE	Water-based Pure Acrylic paint
COLOUR	White & Colours
FINISH	Mid Sheen
USES	Interior use in Kitchens and bathrooms
FEATURES	Protection against fungal and algal growth Resistance to detergent & soap
APPLICATION DATA	
METHOD	Roller , brush, air and airless spray
THEORETICAL COVERAGE	12-15 m ² /liter at dry film thickness of 30 microns (Based on white colour) The actual coverage will depend on the surface texture
PREPARATION OF PAINT	Stir well so that it is uniformly mixed. Avoid excessive thinning.
DILUTION	Use clean water (10 % by volume)
SURFACE PREPARATION	Clean the surface by removing chalk dust, dirt, oil, carbon particles and any other foreign matter. Wipe the surface thoroughly before applying paint. Wash with mild detergent and water for old painted surfaces.



TECHNICAL DATA SHEET FOR
NIPPOLAC KITCHEN AND BATHROOM PAINT

DRYING TIME	Touch Dry	10 -15 minutes at 30 °C ± 2 °C and RH 65 % ± 5%
	Recoating	1 hour at 30 °C ± 2 °C and RH 65 % ± 5%
RECOMMENDED UNDER COAT	Nippolac Acrylic Filler, Nippolac Acrylic Wall Filler, To waterproof the surface, apply two coats of Nippolac Waterproofing compound before applying Nippolac Kitchen & Bathroom paint.	
CLEANING	All equipment should be cleaned with water immediately after use.	
GENERAL INFORMATION		
SOLID CONTENT	50 ± 2 % by weight	
SPECIFIC GRAVITY	1.30 ± 0.05 kg/litre	
PACKING	1 ltr, 4 ltr, 10ltr , 20 ltr & 200 ltr	
SHELF LIFE	Up to 5 years in a tightly sealed container	
STORAGE	Store in secure dry conditions inaccessible to children and animals. Containers should be kept tightly closed during storage. Avoid spillage and contamination. Do not empty into drains or water courses.	
PRECAUTIONS	Ensure good ventilation during application and drying of paint. Avoid direct contact with sensitive skin. Use appropriate personal protective equipment.	

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice

Enquiries Contacts :

Nippon Paint Lanka (Pvt) Ltd.
Nippolac Towers,
69A, Buthgamuwa Road,
Rajagiriya,
Sri Lanka.
Phone +94-114-356900
Fax +94-114-356909
E-mail: colombo@nipponpaint.com.lk
Web : www.nipponpaint.com.lk